

Technical data sheet for

ELECTRIC RANGE STATIC OVEN 900mm

RN8610E, RN8613E, RN8616E, RN8619E

- Heavy-duty construction
- 2.4kW open radiant elements
- Optional hot plate elements
- 300mm, 600mm and 600mm griddle plate options
- GN 2/1 6.5kW electric static oven
- Drop down door
- Stainless steel exterior
- Easy clean
- Easy service
- Fully modular

Overall Construction

- Galvanized steel chassis
- Welded hob with 1.5mm 304 stainless steel bull nose
- Splashback and hob sides 1.2mm 304 stainless steel
- Front panels and oven sides 0.9mm 304 stainless steel
- 150mm legs in 63mm dia. heavy-duty 1.2mm 304 stainless steel with adjustable feet

Сооктог

- 2.4kW open radiant elements in heavy-duty welded element frames
- Vitreous enamelled element module and hob spill trays
- Hot plate elements with machine finished 8mm steel plate (optional extra)
- 12mm thick mild steel griddle plates
- 2.5mm 304 stainless steel griddle splash guards
- Aluminised steel internal construction

Griddle sections are standard on RH side. Available on LH side or centre to order.

OVEN

- Fully welded and vitreous enamelled oven liner
- GN 2/1 capacity with 4 position racking
- Heavy-duty easy remove heavy wire chrome rack supports
- Cast iron even heat oven sole plate
- 6.5kW heating elements
- Welded frame drop down door with heavy-duty spring hinge system
- 0.9mm 304 stainless steel door outer
- 1.0mm press formed vitreous enamelled door inner
- High density fibreglass insulated
- Stay cool stainless steel door handle with cast metal handle mounts
- Supplied with two chrome wire oven racks

Controls

- · Large easy use control knob heat resistant reinforced
- Easy view control settings on knob

Сооктор

- Radiant elements with energy regulator controls
- Hot plate elements with energy regulator controls
- 50-320°C thermostat per 300mm griddle section
- Indicator lights for power and heating for each element control

OVEN

- Separate temperature and top heat power regulation controls
- 50-320°C thermostatic control
- Lo-Hi top heat control
- Indicator lights for power and heating

Cleaning and Servicing

- All models with easy clean stainless steel external finish
- Removable vitreous enamelled element module and hob spill trays
- Hinge up element and griddle sections
- Removable oven racking and sole plate
- $\bullet\,$ Easy clean vitreous enamel oven and door inner
- Door hinge spring adjustable on unit (door outer removed)
- Door disengages for lift off removal and increased service access
- All parts front accessible from installed position
- Access to all parts from front of unit

Technical data sheet for

ELECTRIC RANGE STATIC OVEN 900mm



Specifications

Сооктор

2.4 kW Open Radiant elements 2.0 kW Hot Plate elements

3.6 kW Griddle elements (per 300mm griddle section)

4 5kW bottom heat element 2.0kW top heat element

Electrical requirements

RN8610E 20.9 kW RN8613E 19.7 kW RN8616E 18.5 kW RN8619F 17 3 kW

Electrical connection

20.9 kW max

400-415Vac, 50/60hz, 3P+N+E

I 129 3A max

L2 29.3A max

L3 28.3A max

GRIDDLE PLATE

300mm Griddle cooking surface 292mm x 475mm, 1387cm2

600mm Griddle cooking surface 592mm x 475mm, 2812cm2

900mm Griddle cooking surface 892mm x 475mm, 4237cm2

OVEN DIMENSIONS

Width 665mm

Depth 650mm

Height 400mm

Rack size 650mm x 600mm

Rack positions 4

Electrical connection

69mm from RH side. 484mm from rear. and 150mm from floor

DIMENSIONS

Width 900mm

Depth 805mm

Height 915mm

Incl. splashback 1130mm

PACKING DATA

1.02m3

Width 940mm

Depth 865mm

Height 1255mm

OPTIONS AT EXTRA COST

Hot plate elements (replace individual open radiant elements)


Ribbed griddle plates

Joining caps


Castors

Plinth mounting

RN8610E, RN8613E, RN8616E, RN8619E




RN8610E



RN8613E



RN8616E



RN8619E



MOFFAT

Australia www.moffat.com.au New Zealand www.moffat.co.nz

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone 03-9518 3888 Facsimile 03-9518 3833 vsales@moffat.com.au

New South Wales Telephone 02-8833 4111 nswsales@moffat.com.au

South Australia Telephone 03-9518 3888 vsales@moffat.com.au

Queensland Telephone 07-3630 8600 qldsales@moffat.com.au

Western Australia Telephone 08-9562 0263 jberent@moffat.com.au

New Zealand Moffat Limited

Christchurch Telephone 03-389 1007 sales@moffat.co.nz

Auckland Telephone 09-574 3150 sales@moffat.co.nz



MOFFAT.

ISO9001

All Waldorf products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Limited Moffat/4639/BH/1M/8.05



